

Product data sheet

Characteristics

PDL354RDMLED-VW

PDL Iconic, dimmer, 300M, LED, rotary, 350 W, Vivid White



Main

Range	PDL Iconic
Product or component type	Dimmer
Device presentation	Mechanism
Colour tint	Vivid white (VW)
Type of packing	Box
Load type	Dimmable LED - 350 W - 240 V AC Incandescent - 350 W - 240 V AC Low voltage halogen lamp with electronic transformer - 350 W - 240 V AC Dimmable fluocompact lamp - 150 W - 240 V AC Dimmable fluorescent - 150 W - 240 V AC






Complementary

Range compatibility	PDL Iconic
Control type	Rotary knob
Fixing mode	Clip-in
Surface finish	Glossy
Ambient air temperature for storage	0...60 °C
Dimmer control	315° rotary setting
[Ie] rated operational current	1.5 A
[Ue] rated operational voltage	220...240 V AC 50 Hz 1 W
Function available	Brightness adjustment
Protection type	Short-circuit
Ambient air temperature for operation	0...45 °C
Relative humidity	0...90 %
Connections - terminals	Flying leads
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom
Height	22.5 mm
Width	22.5 mm
Depth	39 mm
Embedding depth	37 mm

Environment

Derating factor	1 deviceswithout derating 2 deviceswith derating factor 3 deviceswith derating factor
Standards	AS/NZS 60669.2.1

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information