

Product data sheet

Characteristics

PDL381M10PML-VW

Switch 300 Series Mechanism - Momentary -
1-or 2-way - Marked PRESS - 250 V - 10 A -
Vivid White



Main

Range of product	PDL Iconic
Product or component type	Switch
Device presentation	Mechanism
Provided equipment	Rocker dolly Switch LED
Device application	Lighting
Colour	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Load type	Inductive Light Fluorescent lamp
Light source	LED 60 mW

Complementary

Switch function	1/2-way
Type of operator	Momentary
Actuator	Rocker
Fixing mode	Locking bar
Marking	With horizontal line image
Surface finish	Matt
Surface treatment	Untreated
Rated current	10 AX at 250 V AC 50 Hz
Electrical durability	20000 cycles conforming to AS/NZS 60669
Connections - terminals	4 screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1.5 mm ² for stranded cable(s) 1.5 mm ² for flexible cable(s) 1.5 mm ² for rigid cable(s)
Wire stripping length	10 mm
Local signalling	LED warm white optional
Material	PC (polycarbonate): housing PA66: housing PC (polycarbonate): dolly ABS (acrylonitrile butadiene-styrene): dolly
Height	23 mm
Width	23 mm
Depth	32 mm
Net weight	0.016 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient air temperature for storage	0...60 °C
Dielectric strength	20000 V
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Product certifications	RCM

Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	 Product Environmental Profile