

# **HDMI DA 1:4 Rack Module**

## **Theatrixx**





#### **#XVVRM-HDMIDA**

The HDMI DA 1:4 Rack Module is a unit option for the 8-Bay Reversible Rackmount Converter system. The module can be inserted in the 8-Bay Frame in either direction, allowing the inputs/outputs to be positioned either at the front or the back of the unit depending on the application. There are no exposed PCBs as all modules are enclosed, and therefore protected against static shock, dust and general wear and tear. Gold-plated, redundant spring pins with magnetic retention deliver DC power to the modules, meaning no messy cabling and external power bricks are needed.

## Connections

**Video Input** 

HDMI 2.0 type A with lock system

**Video Output** 

4 x HDMI 2.0 type A with lock system Individual downscaling per port

# Supported Signals

**Format Support** 

HDR 4K/2K @ 60 fps (4:2:0 10 bits) 4K/2K @ 60 fps (4:4:4 8 bits)



	HDCP Compliance	HDCP 2.2/1.4
	Video Bandwidth	Single-link 600 MHz (18 Gbps)
Physical	Embedded Audio Support	DTS-HD Master Audio, Dolby TrueHD Dolby Digital, DTS, LPCM
	Height	121.5 mm (4.78 in)
	Depth	225 mm (8.85 in)
	Width	41 mm (1.61 in)
	Weight	710 g (1.56 lbs)
Environmental	Operating Temperature	0-40° C
	Relative Humidity	0 -90 % non-condensing
Power Requirements	Power Supply	Reversible redundant power fed by TXVV-RF8 (8-Bay



Rackmount Frame)

**Power Consumption** 

20 W

**Operational Voltage** Range

12 VDC

In the box

Theatrixx Reversible Module HDMI DA 1:4

Certifications









DESIGNED & MANUFACTURED IN CANADA 🍁