



SDI to Fiber Rack Module

Theatrical



#XVVRM-SDI2FIBER

The SDI to Fiber Rack Module is a unit option for the 8-Bay Reversible Rackmount Converter system. The module can be inserted in the 8-Bay Frame in either direction, allowing the inputs/outputs to be positioned either at the front or the back of the unit depending on the application. There are no exposed PCBs as all modules are enclosed, and therefore protected against static shock, dust and general wear and tear. Gold-plated, redundant spring pins with magnetic retention deliver DC power to the modules, meaning no messy cabling and external power bricks are needed.

Connections

Video Input

3G/HD/SD SDI BNC with reclocked loop-thru.

Video Output

Optical SDI on ST/OpticalCON DUO/OpticalCON QUAD, Multimode or Singlemode (see ordering information)

Supported Signals

Video Format

3G-SDI Level A and B, HD-SDI, SD-SDI with embedded audio



SMPTE Standards

425 M Level A & B, 424 M, 292 M, 259 M

Physical

Height

121.5 mm (4.78 in)

Depth

225 mm (8.85 in)

Width

41 mm (1.61 in)

Weight

710 g (1.56 lbs)

Environmental

Relative Humidity

0 % to 90 % non-condensing

Power Requirements

Power Supply

Reversible redundant power fed by TXVV-RF8 (8-Bay Rackmount Frame)

Power Consumption

20 W

Operational Voltage Range

12 VDC

In the box



Theatrixx Reversible Module SDI to Fiber

Ordering information

Option 1

Singlemode (S)
Multimode (M)

Option 2

ST Connector (1)
OpticalCON DUO (2)
OpticalCON QUAD (3)

Certifications



DESIGNED & MANUFACTURED
IN CANADA 