



12G-SDI to Fiber Rack Module

Theatrical



#XVVRM-
SDI2FIBER-12G

The 12G-SDI to Fiber Rack Module is a unit option for the 8-Bay Reversible Rackmount Converter system. The module can be inserted in the 8-Bay Frame in either direction, allowing the inputs/outputs to be positioned either at the front or the back of the unit depending on the application. There are no exposed PCBs as all modules are enclosed, and therefore protected against static shock, dust and general wear and tear. Gold-plated, redundant spring pins with magnetic retention deliver DC power to the modules, meaning no messy cabling and external power bricks are needed.

Connections

Video Input

12G/6G/3G/HD/SD SDI BNC
with reclocked loop-thru.

Video Output

Optical SDI on ST/OpticalCON DUO/ OpticalCON
QUAD,
Multimode or Singlemode.
(see ordering information)

Supported Signals

Video Format

12G/6G/3G-SDI Level A and B, HD-SDI, SD-SDI with
embedded audio



SMPTE Standards

2082-1, 2082-10, 425 M Level A & B, 424 M, 292 M, 259 M

Physical

Height

121.5 mm (4.78 in)

Depth

225 mm (8.85 in)

Width

41 mm (1.61 in)

Weight

710 g (1.56 lbs)

Environmental

Relative Humidity

0% to 90% non-condensing

Power Requirements

Power Supply

Reversible redundant power fed by TXVV-RF8 (8-Bay Rackmount Frame)

Power Consumption

20 W

Operational Voltage Range

12 VDC



In the box

Theatrixx Reversible Module Fiber to SDI

Ordering information

Option 1

Singlemode (S)
Multimode (M)

Option 2

ST Connector (1)
OpticalCON DUO (2)
OpticalCON QUAD (3)

Certifications



DESIGNED & MANUFACTURED
IN CANADA 