



DATASHEET

ACONTROL 6 ROOM CONTROL

*Control, route and mix audio across
multi-space venues.*

KEY FEATURES

Multi-layer programmable remote controller with TCP/IP connectivity over standard shared Ethernet. Configurable as local room/area controller for shared and local audio feeds, or for personal monitoring giving musicians the ability to control their own monitor sound.

There are 6 layers of control, accessed via softkeys, allowing control of 36 individual channels.

- 6 Push 'n' Turn Rotary encoders
- 6 Layers
- 18 Soft-touch panel keys
- 6 TFT Displays
- PoE or external 12V PSU

FRONT PANEL

18 x Backlit buttons

6 x Dual function encoders

6 x Colour LCD displays (Dimmable)

1 x Dimmer control

1 x Programmable 'Alt view' button

REAR PANEL

1 x Fast Ethernet connection - etherCON RJ45 (PoE)

1 x 12V DC power input



4REA4 is a revolution in audio mixing for installed sound. Built on DiGiCo's world class reputation for the finest mixing consoles, 4REA4 helps you integrate your systems better than ever before.

The 4REA4 centralised DSP engine is the hub of the system containing powerful signal processing, expansion slots and connectivity to input/output modules, controllers and other consoles.



CONTROL 6

ROOM CONTROL



A&E SPECIFICATION

The six-channel controller shall be designed to desktop mount or fix to a microphone stand using an optional adapter. It shall be powered either via PoE or the supplied 12VDC adapter.

Connection to the system processor shall be via standard Fast Ethernet. The functionality of the controls shall be determined by the system software. The controller will be supplied with a default name and address which can be changed in software. It shall be possible to return to the default name and address using a recessed reset switch on the rear panel.

The dimmer switch shall step through different illumination levels for the buttons and screens for use in different illumination environments.

The dimensions of the controller shall be:

250 (w) x 208 (h) x 98 (d) mm

9.84 (w) x 8.18 (h) x 3.85 (d) inches

Unpacked Weight: 4Kgs. (8.9lbs.)

The six-channel controller shall be a DiGiCo ACONTROL6.



SPECIFICATIONS

Network: Fast Ethernet 100Mbps

Ext DC In: +12 V, 2.5A


POE+ 802.3af (15.4W at source)

Operating Temperature Range: 0°C to 35°C (32°F to 95°F)

Power Consumption: 5W

Built on years of live audio experience and working closely with our customers, 4REA4 has been designed to meet the expanding performance requirements of large performance venues, conference centres, cruise ships, houses of worship, theatres, music venues and shared stages at festivals.

All dimensions in mm



DiGiCo
www.digico.biz