

# HMI 18000W/SE GX51



#### Product features and benefits

- High intensity light providing true color performance with a CRI>90
- Longer life with heat dissipating round moly-foil design on lamps  $\geq 6000W$
- Mechanically robust with eXtreme Seal (XS) technology, up to 450°C at the pinch seal
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only 1°K/hr
- Dimmable down to 40% with stable color using many electronic ballasts
- High energy efficiency providing up to 100 LPW
- HMI EVENT types offer enhanced brightness and color control as well as UV-stop technology

#### Areas of application

- Studio, TV and film
- Professional Photography
- Solar Simulation

### Technical data

## General product information

| Product Number        | 54324  |  |  |  |
|-----------------------|--|--|--|--|
| Product Name          | HMI18000WSEGX51 1/CS 1/SKU   |  |  |  |
| Ordering Abbreviation | HMI 18000W/SE GX51   |  |  |  |
| Brand Name            | OSRAM  |  |  |  |
| Family Brand Name     | НМІ  |  |  |  |
| General Description   | 18000 watt, metal halide, single-ended, GX51 base,<br>90 CRI, 6000K  |  |  |  |
| Application           | Film, TV & Video Production. Studio Lighting   |  |  |  |
| Product Remark        | <ul> <li>SE=Single Ended</li> <li>s (Operating Position) = Vertical, base down</li> <li>Optimized lamp eXtreme Seal (XS) technology<br/>to withstand interior base temperatures of up<br/>to 450 degrees celsius.</li> </ul> |  |  |  |

## **Electrical data**

| Nominal Wattage | 18000 W |
|-----------------|---------|
| Nominal Voltage | 225 V   |
| Current (A)     | 88 A    |
| Type of Current | AC      |

## Light technical data

| Luminous Flux                  | 1600000 lm |  |
|--------------------------------|------------|--|
| Luminous Efficacy (lm/W)       | 100 lm/W   |  |
| Light Center Length - LCL (mm) | 260 mm     |  |
| Color Temperature              | 6000 К     |  |
| Color Rendering Index          | 90         |  |
| Average Rated Life             | 350 h      |  |

# Physical attributes

| Base                        | GX51 Mogul Bipost |  |
|-----------------------------|-------------------|--|
| Bulb Shape T31              |                   |  |
| Maximum Overall Length (mm) | 495 mm            |  |
| Length l max. (mm)          | 495 mm            |  |
| Diameter d (in)             | 3.937 in          |  |
| Diameter d (mm)             | 100.00 mm         |  |
| Distance a (mm)             | 260 mm            |  |
| Electrode Gap - cold (mm)   | 44 mm             |  |

# Product datasheet

| Reflector Coating             | 100.00     |
|-------------------------------|------------|
| Additional product data       |            |
| Operating Position            | s135       |
| Maximum Base Temperature (°C) | 450 C      |
| Cooling                       | Convection |
| Hot Restart                   | Yes        |
| Lamp Type                     | SINGLE END |

#### Packaging Information

| Product number | EAN/UPC       | Packaging           | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 54324          | 4008321098955 | Shipping box (Case) | 1        | 28.1 in x 9.4 in x 9.4 in    | 7.2 lb       |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.