Product data sheet Characteristics

EVB1A7PAKI

EVlink Smart Wallbox - 7.4 kW - Attached cable T1 - Key





Commercial status

To be discontinued on: 31 December 2021

Main

| EVlink | |
|--------------------------------|---|
| EVlink Smart Wallbox | U |
| Charging station | 5 |
| EVB1 | |
| 1P + N for power circuit | ‡ |
| Wall-mounted Pedestal mount | ilo Hillish |
| Standard | |
| 220240 V AC 50/60 Hz | |
| 7.4 kW 32 A 222240 V | i c |
| Key | E |
| | EVlink Smart Wallbox Charging station EVB1 1P + N for power circuit Wall-mounted Pedestal mount Standard 220240 V AC 50/60 Hz 7.4 kW 32 A 222240 V |

Complementary

| Socket-outlet number | 1 | |
|-----------------------------|--|---|
| Output type | Right side T1 attached cable / silver plated contacts 4.5 m | |
| Earthing system | Compatible IT with additional isolation transformer on the power supply TN-S | : |
| Number of inputs | 6 | |
| Connector type | RS485 for metering Modbus 3 RJ45 for Ethernet LAN connection | |
| Input type | Binary for power limitation closing contact Binary for delayed charging closing contact | |
| Control type | can be controlled by remote 1 multi-colour illuminated push-button, function: stop/restart | |
| Local signalling | 1 multi-colour LED, function: status indication | |
| Communication port protocol | OCPP 1.6 | |
| Configuration /Architecture | Standalone Clustured architecture | |

| Operation and maintenance | Diagnosis capabilities Load management Charge detail records |
|---------------------------|--|
| Web server | Embedded |
| Ethernet service | Configuration via web server |

Environment

| Ziivii oiiiiioiit | |
|---------------------------------------|------------------------------|
| Standards | IEC 61851-1 |
| | IEC 62196-1 |
| | IEC 61851-22 |
| | IEC 62196-2 |
| Product certifications | CE |
| | CB |
| | RCM |
| IP degree of protection | IP54 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |
| Ambient air temperature for operation | -3050 °C |
| Ambient air temperature for storage | -4080 °C |
| Relative humidity | 595 % |
| Product weight | 7.7 kg |
| Colour | White (RAL 9003) |
| | Grey (RAL 7016) |
| | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|----------|
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 9.722 kg |
| Package 1 Height | 27 cm |
| Package 1 width | 40 cm |
| Package 1 Length | 54 cm |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|--|
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |