

The Leader in Touring Technology, Now Coming to a Building Near You!



**Powerful, bidirectional
ArtNet/sACN - DMX data
conversion, patching and
merging**

- 4 DMX Universes
- Simple, intuitive feature set, control, management, via web interface or ProPlex Software
 - Easily manage and route DMX channels for multiple IQs
 - Monitor and patch all RDM devices in the system from one interface
- Pluggable Terminal Block (PTB) screw terminals for bare-wire, installation flexibility
- Complete range of DIN Rail Devices and Drives to make a complete system!



Worldwide Exclusive Distribution

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

New York
+1 201.896.8600

tmb
www.tmb.com

Toronto
+1 519.538.0888

Beijing
+86 10.8492.1587

Riga
+37 16.868.8955

Specifications

Part Number	PPIQDIN14DA
RDM support	Yes
Operating Voltage	24 VDC (Requires external power supply)
Power Consumption	10W
Number of DMX ports	4
Number of sACN/ArtNet universes	1
Signal processing	Art-Net or sACN to DMX512 converter
Power Input	Pluggable Terminal Block (PTB) 2-terminal ¹
Ethernet type	10 / 100 Base-T
Ethernet port	RJ45
DMX ports	4x Pluggable Terminal Block (PTB) 3-terminal ¹
Configuration	Use built-in webserver or dedicated software
Operating Temp.	-22 to +104 °F [-30 to +40 °C]
Dimensions (HxWxD)	1.55 x 4.1 x 3.63 in [39.5 x 104 x 92.3 mm]
Weight	6.13 oz [174 g]

¹ Included

