

IP65 DMX Opto-Splitters for outdoor use



- IP65 rated, intended for temporary installations
- 1 optically isolated DMX input, 6 optically isolated DMX outputs and 1 DMX signal thru
- Power and all data connections hard-wired to internal screw terminals
- All cable entries via IP65 cable glands

Technical Specifications		
Part Number	PPDDS1X6IP65MD	PPDDS1X6IP65MR
Protocols	DMX 512A	DMX 512A, RDM
DMX Inputs	1	
DMX Outputs	6	
DMX Thru	1	
Input/Output Isolation	Optical up to 1000V	
Output/Output Isolation	Optical up to 1000V	
AC Power	90-264V, 50-60 Hz	
Operating Temperature	-40° to +122°F	
Operating Humidity	10-85%	
Cooling	Convection	
Power Cable Outside Diameter	0.18-0.4" [4.5-10 mm]	
DMX Cable Outside Diameter	0.12-0.28" [3-7 mm]	
Dimensions (LxWxH)	7.75 x 7.5 x 3.9 in [197 x 190 x 98 mm]	
Weight	5 lbs. [2.3 kg]	
Connectors	Internal screw terminals	



Worldwide Exclusive Distribution

sales@tmb.com

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

tmb
www.tmb.com

New York
+1 201.896.8600

Beijing
+86 10.8492.1587

Toronto
+1 519.538.0888