

The Leader in Touring Technology, Now Coming to a Building Near You!



**Optically isolated DMX
Splitter with 1 input, 4
outputs**

- 2ms DMX regeneration, automatically fixes “bad” DMX signals
- Versions available with or without RDM
- Pluggable Terminal Block (PTB) screw terminals for bare-wire, installation flexibility
- Complete range of DIN Rail Devices and Drives to make a complete system!



Worldwide Exclusive Distribution

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

New York
+1 201.896.8600

tmb
www.tmb.com

Toronto
+1 519.538.0888

Beijing
+86 10.8492.1587

Riga
+37 16.868.8955

Specifications		
Part Number	PPDDSDIN14RA	PPDDSDIN14MDA
RDM support	Yes	No
Operating Voltage	24 VDC (Requires external power supply)	
Power Consumption	10W	
Number of Inputs	1	
Number of Outputs	4 + 1 Thru	
Number of Universes	1	
Power Input	Pluggable Terminal Block (PTB) 2-terminal ¹	
Data Input	Pluggable Terminal Block (PTB) 3-terminal ¹	
Data Thru	Pluggable Terminal Block (PTB) 3-terminal ¹	
Data Outputs	4x Pluggable Terminal Block (PTB) 3-terminal ¹	
Operating Temp.	-22 to 104 °F [-30 to +40 °C]	
Dimensions (HxWxD)	1.55 x 4.1 x 3.63 in [39.5 x 104 x 92.3 mm]	
Weight	6.13 oz [174 g]	

¹ Included

