

[Click to Print This Page](#)



## E-VISION LASER 4K DIGITAL PROJECTOR

THE VISIONARIES CHOICE




### E-Vision Laser 4K-UHD Black

**7,000 ANSI / 7,500 ISO Lumens | Contrast Ratio: 10,000:1 (Dynamic Black) 1,000:1 native | Part Number: 118-150**

#### Key Specifications:

<b>Colour System:</b>	Laser Phosphor with colourwheel
<b>Display Type:</b>	1 x 0.66" WQXGA+ TRP UHD DMD™
<b>DMD Specification:</b>	Display resolutions 4K-UHD (3840 x 2160) or WQXGA+ (2716 x 1528) 8.3 megapixels on screen at 4K-UHD Fast transit pixels for smooth greyscale and improved contrast.
<b>Aspect Ratio:</b>	16:9
<b>Fill Factor</b>	Not applicable: Smooth Picture DMD™
<b>Key Features:</b>	<b>Video &amp; Graphics Processing</b> <ul style="list-style-type: none"><li>• HDR processing</li><li>• Two projectors in one - 4K-UHD and WQXGA+.</li><li>• DisplayPort 1.2.</li><li>• 2 x HDMI 2.0.</li><li>• 2 x HDMI 1.4b for Dual Pipe processing and Frame Sequential 3D format.</li><li>• Sequential Processing: 3D via single HDMI 1.4b input.</li><li>• Dual Pipe Processing: 3D Left and Right Eyes via two HDMI 1.4b inputs.</li><li>• Synchronisation of active glasses.</li><li>• 3G-SDI with loop-through.</li><li>• DICOM simulation mode.</li></ul>

	<div><div><b>Geometry Correction</b><ul style="list-style-type: none"><li>• Cornerstone, Vertical &amp; Horizontal Keystone, Pincushion &amp; Barrel, Arc and Image Rotation.</li><li>• Non-linear warp.</li><li>• Digital zoom, pan and scan.</li><li>• Blanking control for custom input window sizing.</li><li>• Scaling available for fixed aspect ratio screens.</li><li>• Unscaled processing for pixel mapped display.</li></ul></div><div><b>Edge Blending</b><ul style="list-style-type: none"><li>• Blending control available for all sides with width control.</li><li>• Correction for non-active pixels at the edge of the display.</li></ul></div><div><b>Picture in Picture</b><ul style="list-style-type: none"><li>• Two sources can be displayed simultaneously using 2D inputs: either picture in picture (PIP), or side by side (PBP), with original aspect ratios maintained.</li></ul></div><div><b>HDBaseT® Interface</b><ul style="list-style-type: none"><li>• Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable.</li><li>• Allows projector to be placed up to 100m from source with low cost cabling.</li><li>• Supports up to 4K UHD 3840 x 2160@60Hz 4:2:0 or 4K UHD 3840 x 2160@30Hz 4:4:4</li></ul></div><div><b>Colour Processing</b><ul style="list-style-type: none"><li>• Four colour modes available.</li><li>• Powerful seven point colour correction for accurate colour matching with presets.</li><li>• Easy colour temperature selection.</li><li>• Manual seven point colour adjustment.</li><li>• Traditional lifts and gains.</li></ul></div><div><b>Projector Controller Software</b><ul style="list-style-type: none"><li>• Intuitive user interface for network control.</li><li>• Simultaneous control of user-defined groups of projectors.</li><li>• At-a-glance monitoring of projector status.</li></ul></div><div><b>Projector Automation</b><ul style="list-style-type: none"><li>• Real-time clock provides daily on/off automation.</li><li>• E-mail alerts for system status.</li></ul></div></div>		
Source Compatibility	<div><p>2D graphics standards up to 4K-UHD 3840 x 2160 resolution at 60Hz via HDMI 2.0, HDBaseT (4:2:0) and DisplayPort inputs.</p><p>3D graphics standards up to WQXGA at 120Hz DualPipe via HDMI 1.4b inputs.</p><p>3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.</p><p><b>WQXGA+ mode</b></p><p>2D sources up to WQXGA+ at 120Hz can be displayed scaled to fit WQXGA+.</p><p>3D sources up to WQXGA at 120Hz can be displayed scaled to fit WQXGA+.</p><p><b>4K-UHD mode</b></p><p>2D sources up to 4K-UHD will be displayed scaled to fit 4K-UHD.</p><p><b>Auto mode</b></p><p>Sources greater than WQXGA+ will be displayed scaled to fit 4K-UHD.</p><p>Sources up to WQXGA+ will be displayed scaled to fit WQXGA+.</p></div>		
Inputs/Outputs	<table><tr><td>Video &amp; Computer</td><td>Communication &amp; Control</td></tr></table>	Video & Computer	Communication & Control
Video & Computer	Communication & Control		

	Type	Connector	Qty	Type	Connector	Qty												
	DisplayPort 1.2 (2D)	DisplayPort	1	3D Sync Out	BNC													
	HDMI 1.4b (3D)	HDMI	2	3D Sync In	BNC													
	HDMI 2.0 (2D)	HDMI	2	LAN	RJ45	1												
	3G-SDI in (2D)	BNC	1	RS232	9-pin D	1												
	3G-SDI out	BNC	1	Wired Remote	Sub	2												
	HDBaseT (see LAN) (2D)	RJ45	1	12V Trigger	3.5mm	1												
				3D Sync IR Out	Stereo	1												
				<b>NOTE: One of the LAN ports is shared with HDBase-T.</b>	Jack	2												
					3.5mm	1												
					Stereo													
					Jack													
					BNC													
<b>3D Formats Supported</b>	Frame Sequential Dual-Pipe																	
<b>HDTV Formats Supported</b>	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz, 100Hz, 120Hz) 1080i (50Hz, 60Hz) 720p (50, 60Hz) 2K (24Hz, 25Hz, 30Hz, 50Hz, 60Hz) 4K-UHD (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)																	
<b>Computer Compatibility</b>	<b>2D</b> 4K-UHD up to 60Hz. WQXGA+ up to 120Hz. <b>3D</b> Supported formats will be displayed within WQXGA+.																	
<b>Bandwidth</b>	498 megapixels per second via DisplayPort and HDMI 2.0.																	
<b>Remote Control</b>	Addressable IR remote control, wireless and wired. On-Board keypad																	
<b>Automation Control</b>	Crestron RoomView® Connected PJLink Class 1 LAN RS232 AMX (Device Discovery) Served web pages (projector status, projector control, Crestron RoomView®, network settings, alert mail setup, time setup, error log, On Screen Display)																	
<b>Colour Temperature</b>	3200K to 9300K																	
<b>Operation</b>																		
<b>illumination Type</b>	Laser Light Source																	
<b>Typical illumination Life</b>	20,000 hours																	
<b>Lenses</b>	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>0.38 :1 fixed</td><td>117-341</td><td>0.68m - 2.44m</td><td>Depends on image size, see Installation Guide.</td></tr><tr><td>0.74 - 0.93 :1 zoom</td><td>115-339</td><td>1.02m - 12.7m</td><td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2</td></tr></table>						Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.	0.74 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)															
0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.															
0.74 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2															

			(R) frame
	0.76 :1 fixed	112-499	0.81m - 5.08m none
	1.24 - 1.78 :1 zoom	112-500	1.33m - 11.73m Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
	1.71 - 2.25 :1 zoom	112-501	1.83m - 14.9m Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
	2.2 - 3.67 :1 zoom	112-502	2.36m - 24.2m Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
	3.54 - 5.36 :1 zoom	112-503	3.8m - 35.35m Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
	5.24 - 8.27 :1 zoom	112-504	5.59m - 54.8m Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,			
<b>Lens Mount</b>	Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).		
<b>Mechanical Mounting</b>	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet		
<b>Orientation</b>	<b>Table Top or Inverted:</b> Yes <b>Pointing Up:</b> Yes <b>Pointing Down:</b> Yes <b>Roll (Portrait):</b> Yes		
<b>Power Requirements</b>	100-130VAC and 200-240VAC selectable, 50/60Hz single phase		
<b>Power Consumption</b>	950 W @220 Vac (1000 W @110 Vac)		
<b>Thermal Dissipation</b>	Max 3139 BTU/hour @100 VAC Max 3002 BTU/hour @240 VAC		
<b>Fan Noise</b>	<b>Smooth Picture On:</b> <i>Normal mode:</i> typical 40 (max 42) dBA <i>Eco2 mode:</i> typical 37 (max 39) dBA <b>Smooth Picture Off:</b> <i>Normal mode:</i> typical 38 (max 40) dBA <i>Eco2 mode:</i> typical 34 (max 36) dBA		
<b>Operating/Storage Temperature Operating:</b>	Operating: 5 to 40C (41 to 104F) Storage: -10 to 60C (14 to 140F)		
<b>Operating Humidity</b>	10 to 85% non-condensing		
<b>Weight</b>	28.15 kg / 62 lbs		
<b>Dimensions</b>	L: 59.83 cm x W: 50 cm x H: 21.85 cm L: 23.55 in x W: 19.68 in x H: 8.60 in		
<b>Safety &amp; EMC Regulations</b>	CE, FCC Class A, CCC, UL/cUL, FDA CB, KC, CEL, CECP		
<b>Accessories</b>			

	Accessory	Part No.
	Infrared Remote (replacement)	117-880
*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.		
Downloads	<a href="#">PDF CAD Drawings</a> <a href="#">AUTOCAD Drawings</a> <a href="#">STEP / IGS Drawings</a> <a href="#">Lens CAD Drawings</a>	
User Guide	<a href="#">User Guides</a> <a href="#">Laser Risk Group Document</a> <a href="#">Important Information</a> <a href="#">Important Information (Korean)</a> <a href="#">Control Protocol</a> <a href="#">Ultra Short Throw Lens</a> <a href="#">Ultra Short Throw Lens Installation Guide</a>	



**DIGITAL PROJECTION, LTD**



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



[www.digitalprojection.co.uk](http://www.digitalprojection.co.uk)



**DIGITAL PROJECTION, INC**



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



[www.digitalprojection.com](http://www.digitalprojection.com)



**DIGITAL PROJECTION, CHINA**

**DIGITAL PROJECTION**

A Delta Group Company

Specifications subject to change without notice.  
 ©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



Certificate Number 13629  
 ISO 9001



**Rm A2301, Shaoyaoju 101 North Lane, Shi Ao**

**International Center, Chaoyang District, Beijing 100029,  
PR China**



**T: +86.10.58239771 | F: +86 10 58239770**