

[Click to Print This Page](#)



E-VISION LASER 9000 WU DIGITAL PROJECTOR

THE VISIONARIES CHOICE



E-Vision Laser 9000 WU

9,000 ISO / 8,000 ANSI Lumens | Contrast Ratio: 20,000:1 (dynamic) | Part Number: 120-481

Key Specifications:

Colour System:	Laser Phosphor / 4 Segment (RGBY) Colourwheel / 2x120Hz
Display Type:	1 x 0.67" DarkChip™ DMD™
DMD Specification:	1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	87%
Key Features:	Video & Graphics Processing • HDMI 2.0 for Side by Side, Frame Packing & Top Bottom 3D Formats. • Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources (example 144Hz display). • Synchronisation of active glasses and compatible with polarised glasses • 24p and 1080p native display. • Sealed light engine • DICOM Simulation Mode. • HDR Support • Powerful 7 point colour correction for accurate colour matching Geometry Correction • Cornerstone, Vertical & Horizontal Keystone. • Selectable Aspect Ratios • Digital Zoom

	HDBaseT® Interface • Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable. • Allows projector to be placed up to 100m from source with low cost cabling. • Projector Control via HDBaseT.																																																																								
Source Compatibility	HDMI including Deep Color™ processing. Graphics standards support up to 3840 x 2160 (4K-UHD) & 4096 x 2160 (full 4K) resolution via HDMI Graphics standards up to native 1920 x 1200 resolution @ 60Hz via DVI-D, HDBaseT or VGA Component Video (SD and HD) via RGBHV.																																																																								
Inputs/Outputs	<table><tr><th colspan="3">Video & Computer</th><th colspan="3">Communication & Control</th></tr><tr><th>Type</th><th>Connector</th><th>Qty</th><th>Type</th><th>Connector</th><th>Qty</th></tr><tr><td>HDMI 2.0</td><td>HDMI</td><td>2</td><td>3D Sync Out</td><td>Mini DIN</td><td>1</td></tr><tr><td>DVI-D</td><td>DVI</td><td>1</td><td>3D Sync In</td><td>Mini DIN</td><td>1</td></tr><tr><td>VGA / Analog RGB</td><td>15-pin D-Sub</td><td>1</td><td>LAN</td><td>RJ45</td><td>1</td></tr><tr><td>Component Video</td><td>5 x BNC</td><td>5</td><td>Serial In (RS232)</td><td>9-pin D-Sub</td><td>1</td></tr><tr><td>HDBaseT</td><td>RJ45</td><td>1</td><td>Serial Out (RS232)</td><td>9-pin D-Sub</td><td>1</td></tr><tr><td>Video Out: VGA</td><td>15-pin D-Sub</td><td>1</td><td>Wired Remote In</td><td>3.5mm Stereo Jack</td><td>1</td></tr><tr><td>Audio In: Stereo</td><td>RCA</td><td>2</td><td>Wired Remote Out</td><td>3.5mm Stereo Jack</td><td>1</td></tr><tr><td>Audio In: Stereo</td><td>3.5mm Jack</td><td>1</td><td>12V Trigger</td><td>3.5mm Stereo Jack</td><td>1</td></tr><tr><td>Audio Out: Stereo</td><td>RCA</td><td>2</td><td>USB (power only)</td><td>USB Type A</td><td>1</td></tr><tr><td></td><td></td><td></td><td>USB (Service)</td><td>USB Type B</td><td>1</td></tr></table>	Video & Computer			Communication & Control			Type	Connector	Qty	Type	Connector	Qty	HDMI 2.0	HDMI	2	3D Sync Out	Mini DIN	1	DVI-D	DVI	1	3D Sync In	Mini DIN	1	VGA / Analog RGB	15-pin D-Sub	1	LAN	RJ45	1	Component Video	5 x BNC	5	Serial In (RS232)	9-pin D-Sub	1	HDBaseT	RJ45	1	Serial Out (RS232)	9-pin D-Sub	1	Video Out: VGA	15-pin D-Sub	1	Wired Remote In	3.5mm Stereo Jack	1	Audio In: Stereo	RCA	2	Wired Remote Out	3.5mm Stereo Jack	1	Audio In: Stereo	3.5mm Jack	1	12V Trigger	3.5mm Stereo Jack	1	Audio Out: Stereo	RCA	2	USB (power only)	USB Type A	1				USB (Service)	USB Type B	1
Video & Computer			Communication & Control																																																																						
Type	Connector	Qty	Type	Connector	Qty																																																																				
HDMI 2.0	HDMI	2	3D Sync Out	Mini DIN	1																																																																				
DVI-D	DVI	1	3D Sync In	Mini DIN	1																																																																				
VGA / Analog RGB	15-pin D-Sub	1	LAN	RJ45	1																																																																				
Component Video	5 x BNC	5	Serial In (RS232)	9-pin D-Sub	1																																																																				
HDBaseT	RJ45	1	Serial Out (RS232)	9-pin D-Sub	1																																																																				
Video Out: VGA	15-pin D-Sub	1	Wired Remote In	3.5mm Stereo Jack	1																																																																				
Audio In: Stereo	RCA	2	Wired Remote Out	3.5mm Stereo Jack	1																																																																				
Audio In: Stereo	3.5mm Jack	1	12V Trigger	3.5mm Stereo Jack	1																																																																				
Audio Out: Stereo	RCA	2	USB (power only)	USB Type A	1																																																																				
			USB (Service)	USB Type B	1																																																																				
3D Formats Supported	Frame Packing Side By Side (half) Top and Bottom																																																																								
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz),1080i (50Hz, 60Hz), 720p (50, 60Hz)																																																																								
Computer Compatibility	Up to 1920 x 1200 via DVI-D, HDBaseT, VGA Up to 4096 x 2160 via HDMI																																																																								
Bandwidth	165 MHz on analog RGB 498 Megapixels per second on HDMI																																																																								
Remote Control	IR remote control, wireless and wired. On-Board keypad																																																																								
Automation Control	Crestron RoomView® Connected PJLink - AMX SSDP LAN RS232 - AMX SSDP																																																																								
Colour Temperature	User Selectable																																																																								
Operation																																																																									
illumination Type	Laser Light Source																																																																								
Typical illumination Life	20,000 hours																																																																								
Lenses	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>0.77: 1 fixed</td><td>114-785</td><td>0.4m - 3.1m</td><td>Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05</td></tr></table>	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.77: 1 fixed	114-785	0.4m - 3.1m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05																																																																
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																																																																						
0.77: 1 fixed	114-785	0.4m - 3.1m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05																																																																						

				(L) 0.05 (R) frame
	0.77 - 1.1: 1 zoom (special order - call for info)	119-001	0.67m - 12.1m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
	1.1 - 1.3: 1 zoom	116-207	1m - 9m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
	1.25-1.6 zoom (special order - call for info)	119-430	1.356m - 8.078m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
	1.54 - 1.93: 1 zoom	114-783	0.95m - 11.9m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
	1.93 - 2.91: 1 zoom	114-784	1.2m - 29.8m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
	3.0 - 5.0: 1 zoom	116-208	3m - 20m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,				
Lens Mount	Manual shift, zoom & focus.			
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet			
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes			
Power Requirements	100-240VAC 50/60Hz single phase			
Power Consumption	1000			
Thermal Dissipation	3410			
Fan Noise	Typical 44dBA			
Operating/Storage Temperature Operating:	Operating: 0 to 40C (32 to 104F) >35C switches to Eco Mode Storage: -20 to 60C (-4 to 140F)			
Operating Humidity	10 to 85% non-condensing			
Weight	25 kg / 55.1 lbs			
Dimensions	L: 52.5 cm W: 47 cm H: 22.05 cm L: 20.66 in W: 18.5 in H: 8.68 in			
Safety & EMC Regulations	CE, FCC Class B, UL, CCC, CB, RoHS			
Accessories				
	Accessory		Part No.	
	Infrared Remote (replacement)		117-880	

	<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings Lens CAD Drawings
User Guide	User Guides User Guides (German) User Guides (French) Laser Risk Group Document Important Information Control Protocol



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770

DIGITAL PROJECTION

A Delta Group Company

Specifications subject to change without notice.
©2022 Digital Projection. DLP®, Digital Light
Processing™ and DMD are trademarks of Texas
Instruments, Inc



Certificate Number 13629
ISO 9001

