

[Click to Print This Page](#)



E-VISION LASER 5900 DIGITAL PROJECTOR

THE VISIONARIES CHOICE




E-Vision Laser 5900 WUXGA

5,300 ANSI / 6,000 ISO Lumens | Contrast Ratio: 2,000:1 Native 20,000:1 Dynamic | Part Number: 120-551

Key Specifications:

Colour System:	Laser Phosphor
Display Type:	1 x 0.67" DarkChip™ DMD™
DMD Specification:	1920 x 1200 pixels native resolution. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	
Key Features:	<p>Video & Graphics Processing</p> <ul style="list-style-type: none">• HDMI 1.4a for Side by Side, Frame Packing, Frame Sequential & Top Bottom 3D formats.• Synchronisation of active 3D glasses.• DICOM simulation mode.• Mobile High-Definition Link (MHL™) connection allows mirrored content from smartphones, tablets and other portable consumer electronics devices. <p>Geometry Correction</p> <ul style="list-style-type: none">• Vertical & Horizontal Keystone correction (2D: Vertical $\pm 30^\circ$, Horizontal $\pm 30^\circ$).• Four Corner adjustment.• Selectable 16:9, 4:3, Native, Letterbox and Full Screen aspect ratios.• Digital Zoom +10~-10. <p>HDBaseT® Interface</p>

	<ul style="list-style-type: none">• Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.• Allows the projector to be placed up to 100m from the source with low cost cabling.• HDBaseT® includes audio, Ethernet 100BaseT and RS232/IR control. <p>Colour Processing</p> <ul style="list-style-type: none">• 2 x speed, 3 Segment (GBY) Phosphor wheel.• 2 x 120Hz speed, 4 Segment (RGBY) Colour wheel.• 10-bit colour display.• Powerful seven point colour correction for accurate colour matching.																																																																																																																														
Source Compatibility	Graphics standards up to 1920 x 1200 resolution at 60Hz. Input support for 4K-UHD, 3840 x 2160 and 4096 x 2160 at 60 Hz.																																																																																																																														
Inputs/Outputs	<table><tr><th colspan="3">Video & Computer</th><th colspan="3">Communication & Control</th></tr><tr><th>Type</th><th>Connector</th><th>Qty</th><th>Type</th><th>Connector</th><th>Qty</th></tr><tr><td>HDMI 1.4a</td><td>HDMI</td><td></td><td></td><td></td><td></td></tr><tr><td>HDMI 1.4a + MHL</td><td>HDMI</td><td></td><td></td><td></td><td></td></tr><tr><td>VGA / Analog RGB</td><td>15-pin D-Sub</td><td>2</td><td></td><td></td><td></td></tr><tr><td>VGA / Monitor Out</td><td>15-pin D-Sub</td><td>1</td><td></td><td></td><td></td></tr><tr><td>Composite Video</td><td>RCA</td><td>1</td><td></td><td></td><td></td></tr><tr><td>HDBaseT</td><td>RJ45</td><td>1</td><td>LAN</td><td></td><td></td></tr><tr><td>USB Type A / (5V/1.5A)</td><td>USB Type A</td><td>1</td><td>RS-232C</td><td>RJ45</td><td></td></tr><tr><td>NOTE: The USB is to power WHDI™ interfaces.</td><td></td><td>1</td><td>USB (for Service)</td><td>9-pin D-sub</td><td>1</td></tr><tr><td></td><td></td><td></td><td>3D Sync Out</td><td>Mini B</td><td>1</td></tr><tr><td>Audio:</td><td></td><td></td><td>NOTE: The HDBaseT and LAN ports are not shared.</td><td>VESA 3-PIN mini DIN</td><td>1</td></tr><tr><td>Audio IN L+R</td><td>Phono</td><td>2</td><td></td><td></td><td></td></tr><tr><td>Audio IN L+R</td><td>3.5 mm</td><td>1</td><td></td><td></td><td></td></tr><tr><td>Mic IN</td><td>jack</td><td>1</td><td></td><td></td><td></td></tr><tr><td>Audio OUT (variable)</td><td>3.5 mm</td><td>1</td><td></td><td></td><td></td></tr><tr><td>Speakers</td><td>jack</td><td>2</td><td></td><td></td><td></td></tr><tr><td></td><td>3.5 mm</td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>jack</td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>5W</td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>speaker</td><td></td><td></td><td></td><td></td></tr></table>	Video & Computer			Communication & Control			Type	Connector	Qty	Type	Connector	Qty	HDMI 1.4a	HDMI					HDMI 1.4a + MHL	HDMI					VGA / Analog RGB	15-pin D-Sub	2				VGA / Monitor Out	15-pin D-Sub	1				Composite Video	RCA	1				HDBaseT	RJ45	1	LAN			USB Type A / (5V/1.5A)	USB Type A	1	RS-232C	RJ45		NOTE: The USB is to power WHDI™ interfaces.		1	USB (for Service)	9-pin D-sub	1				3D Sync Out	Mini B	1	Audio:			NOTE: The HDBaseT and LAN ports are not shared.	VESA 3-PIN mini DIN	1	Audio IN L+R	Phono	2				Audio IN L+R	3.5 mm	1				Mic IN	jack	1				Audio OUT (variable)	3.5 mm	1				Speakers	jack	2					3.5 mm						jack						5W						speaker				
Video & Computer			Communication & Control																																																																																																																												
Type	Connector	Qty	Type	Connector	Qty																																																																																																																										
HDMI 1.4a	HDMI																																																																																																																														
HDMI 1.4a + MHL	HDMI																																																																																																																														
VGA / Analog RGB	15-pin D-Sub	2																																																																																																																													
VGA / Monitor Out	15-pin D-Sub	1																																																																																																																													
Composite Video	RCA	1																																																																																																																													
HDBaseT	RJ45	1	LAN																																																																																																																												
USB Type A / (5V/1.5A)	USB Type A	1	RS-232C	RJ45																																																																																																																											
NOTE: The USB is to power WHDI™ interfaces.		1	USB (for Service)	9-pin D-sub	1																																																																																																																										
			3D Sync Out	Mini B	1																																																																																																																										
Audio:			NOTE: The HDBaseT and LAN ports are not shared.	VESA 3-PIN mini DIN	1																																																																																																																										
Audio IN L+R	Phono	2																																																																																																																													
Audio IN L+R	3.5 mm	1																																																																																																																													
Mic IN	jack	1																																																																																																																													
Audio OUT (variable)	3.5 mm	1																																																																																																																													
Speakers	jack	2																																																																																																																													
	3.5 mm																																																																																																																														
	jack																																																																																																																														
	5W																																																																																																																														
	speaker																																																																																																																														
3D Formats Supported	Frame Packing Frame Sequential Side By Side (half) Top and Bottom																																																																																																																														
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz),1080i (50Hz, 60Hz), 720p (50, 60Hz)																																																																																																																														
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz																																																																																																																														
Bandwidth																																																																																																																															
Remote Control	IR remote control, 2 x IR receivers (front sensitivity up to 7m, rear sensitivity up to 10m)																																																																																																																														
Automation Control	LAN control - Crestron RoomView® Connected LAN control - Crestron eControl LAN control - Extron LAN control - AMX SSDP LAN control to RS232 by Telnet																																																																																																																														

	HDBaseT communication Projector status email alerts PJ Link (Class1)										
Colour Temperature	Warm / Normal / Cold										
Operation											
illumination Type	Laser Light Source										
Typical illumination Life	20,000 hours										
Lenses	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>1.15 - 1.9:1</td><td>N/A</td><td>1.5m - 10.0m</td><td>Vert: Fixed Offset 0.65 (U) frame with small variable vertical and horizontal shift</td></tr></table> <p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p>			Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	1.15 - 1.9:1	N/A	1.5m - 10.0m	Vert: Fixed Offset 0.65 (U) frame with small variable vertical and horizontal shift
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)								
1.15 - 1.9:1	N/A	1.5m - 10.0m	Vert: Fixed Offset 0.65 (U) frame with small variable vertical and horizontal shift								
Lens Mount	Manual focus										
Mechanical Mounting	Front/Rear Front/Rear Ceiling Two adjustable front feet, 10° (43mm) Ceiling Mount compatible chassis with 7 off M4 mounting holes										
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes										
Power Requirements	100-240VAC 50/60Hz single phase										
Power Consumption	Normal Mode (100%) 480W @230V 500W @110V Eco Mode (80%) 355W @230V 365W @110V										
Thermal Dissipation	Normal Mode (typical): 1706 BTU/Hour @ 110VAC 1638 BTU/Hour @ 230VAC										
Fan Noise	Normal Mode Typ: 36 dBA / Max: 38 dBA										
Operating/Storage Temperature Operating:	Operating: 0° to 40°C (32F to 104F) Storage: -20° to 60°C (-4F to 140F)										
Operating Humidity	10 to 85% non-condensing										
Weight	10.5 kg / 23.21 lbs										
Dimensions	L: 44.56 cm W: 36.0 cm H: 16.35 cm L: 17.54 in W: 14.17 in H: 6.43 in										
Safety & EMC Regulations	UL/cUL, CB, CCC/CECP, FCC Class B, FDA, CE IEC 60825-1:2007 3R IEC60825-1:2014 Class 1 IEC EN 62471-5 Risk Group 2										
Accessories	<table><tr><td>Accessory</td><td>Part No.</td></tr><tr><td> </td><td> </td></tr></table>			Accessory	Part No.						
Accessory	Part No.										

	Infrared Remote (replacement)	117-880
	*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.	
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings	
User Guide	User Guides User Guides (German) User Guides (French) Laser Risk Group Document Important Information Important Information (German) Important Information (French) Control Protocol Ultra Short Throw Lens Ultra Short Throw Lens Installation Guide	



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA

DIGITAL PROJECTION

A Delta Group Company

Specifications subject to change without notice.
 ©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



Certificate Number 13629
 ISO 9001



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

**International Center, Chaoyang District, Beijing 100029,
PR China**



T: +86.10.58239771 | F: +86 10 58239770