Click to Print This Page





E-Vision Laser 5100 WUXGA

4,500 ANSI / 5,100 ISO Lumens | Contrast Ratio: 2,000:1 Native 20,000:1 Dynamic | Part Number: 120-552

Key Specifications:

Colour System:	Laser Phosphor			
Display Type:	1 x 0.67" DarkChip™ DMD™			
DMD Specification:	1920 x 1200 pixels native resolution. Fast transit pixels for smooth greyscale and improved contrast.			
Aspect Ratio:	16x10			
Fill Factor				
Key Features:	Video & Graphics Processing			
	 HDMI 1.4a for Side by Side, Frame Packing, Frame Sequential & Top Bottom 3D formats. Synchronisation of active 3D glasses. DICOM simulation mode. Mobile High-Definition Link (MHL^M) connection allows mirrored content from smartphones, tablets and other portable consumer electronics devices. 			
	 Geometry Correction Vertical & Horizontal Keystone correction (2D: Vertical ±15°, Horizontal±15°). Four Corner adjustment. Selectable 16:9, 4:3, Native, Letterbox and Full Screen aspect ratios. Digital Zoom +10~-10. HDBaseT® Interface 			

Source Compatibility	CAT5e/6 LAN cable Allows the projecto HDBaseT® includes Colour Processing 2 x speed, 3 Segme 2 x 120Hz speed, 4 10-bit colour displa	r to be placed u s audio, Ethern nt (GBY) Phosp Segment (RGB` y. nt colour corre	up to 1 et 100F hor wh Y) Colo ction fo	ur wheel. or accurate colour matching n at 60Hz.	ow cost cablin	
Inputs/Outputs		3840 X 2100 al	10 409			
mputs/outputs	Video & Computer			Communication & Control		
	Туре	Connector	Qty	Туре	Connector	Qty
	HDMI 1.4a HDMI 1.4a + MHL VGA / Analog RGB VGA / Monitor Out Composite Video HDBaseT USB Type A / (5V/1.5A) NOTE: The USB is to power WHDI™ interfaces. Audio: Audio IN L+R Audio IN L+R Mic IN Audio OUT (variable) Speakers	HDMI HDMI 15-pin D- Sub RCA RJ45 USB Type A Phono 3.5 mm jack 3.5 mm jack 3.5 mm jack 3.5 mm	2 1 1 1 1 1 1 1 2 1 1 2	LAN RS-232C USB (for Service) 3D Sync Out NOTE: The HDBaseT and LAN ports are not shared.	RJ45 9-pin D- sub Mini B VESA 3- PIN mini DIN	1 1 1 1
3D Formats Supported	Frame Packing Frame Sequential Side By Side (half) Top and Bottom					
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz),1080i (50Hz, 60Hz), 720p (50, 60Hz)					
Computer Compatibility	VGA, SVGA, XGA, SXGA, SX	GA+, UXGA, WL	JXGA@	60hz		
Bandwidth						
Remote Control	IR remote control, 2 x IR re	eceivers (front s	sensitiv	vity up to 7m, rear sensitivity	/ up to 10m)	
Automation Control	LAN control - Crestron Roc LAN control - Crestron eCc LAN control - Extron LAN control - AMX SSDP LAN control to RS232 by Te	ontrol	ected			

	HDBaseT commu Projector status e PJ Link (Class1)				
Colour Temperature	Warm / Normal / Cold				
Operation	24×7 OPERATION				
illumination Type	Laser Light Sourc	e			
Typical illumination Life	20,000 hours				
Lenses	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	
	0.5 :1	N/A	0.76m - 3.23m	Vert: Fixed Offset 0.6 (U) frame	
	* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,				
Lens Mount	Manual focus	Manual focus			
Mechanical Mounting	-	ont feet, 10° (43mm)	off M4 mounting holes		
Orientation	Table Top or Inverted: YesPointing Up:YesPointing Down:YesRoll (Portrait):Yes				
Power Requirements	100-240VAC 50/6	100-240VAC 50/60Hz single phase			
Power Consumption	Normal Mode (100%) 480W @230V 500W @110V Eco Mode (80%) 355W @230V 365W @110V				
Thermal Dissipation	Normal Mode (typical): 1706 BTU/Hour @ 110VAC 1638 BTU/Hour @ 230VAC				
Fan Noise	Normal Mode Ty	p: 36 dBA / Max: 38 dBA	A		
Operating/Storage Temperature Operating:	Operating: 0° to 4 Storage: -20° to 6	40°C (32F to 104F) 50°C (-4F to 140F)			
Operating Humidity	10 to 85% non-cc	10 to 85% non-condensing			
Weight	10.5 kg / 23.21 lb	S			
Dimensions		L: 43.71 cm W: 36.0 cm H: 17.71 cm L: 17.2 in W: 14.17 in H: 6.97 in			
Safety & EMC Regulations	UL/cUL, CB, CCC/CECP, FCC Class B, FDA, CE IEC 60825-1:2007 3R IEC60825-1:2014 Class 1 IEC EN 62471-5 Risk Group 2				
	Accessory Part No				
Accessories	Accessory		Part No.		

	*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.
Downloads	PDF CAD Drawings AUTOCAD Drawings
	STEP / IGS Drawings
User Guide	<u>User Guides</u>
	<u>User Guides (German)</u>
	<u>User Guides (French)</u>
	Laser Risk Group Document
	Important Information
	Important Information (German)
	Important Information (French)
	Control Protocol





Specifications subject to change without notice. ©2022 Digital Projection. DLP®, Digital Light Processing[™] and DMD are trademarks of Texas Instruments, Inc



Certificate Number 13629 ISO 9001

PR China

0

T: +86.10.58239771 | F: +86 10 58239770