

Lok-it! 1200 W 80 V/32/P50

Lok-it! | Halogen lamps



Product family benefits

- Optimum use of the generated light in the spotlight



Technical data

Product information

| | |
|-----------------|-----------------|
| Order reference | LOK-IT! 1200W/3 |
|-----------------|-----------------|


Electrical data

| | |
|-----------------|-----------|
| Nominal voltage | 80.0 V |
| Nominal wattage | 1200.00 W |

Photometrical data

| | |
|--------------------------|--------|
| Color temperature | 3200 K |
| Color rendering index Ra | 100 |

Dimensions & weight



| | |
|---------------------------|---------------------------|
| Diameter | 23.0 mm |
| Length | 140.0 mm |
| Light center length (LCL) | 84.0 mm |
| Illuminated field | 14.7*14.5 mm ² |

Lifespan

| | |
|----------|-------|
| Lifespan | 250 h |
|----------|-------|

Capabilities

| | |
|------------------|-----|
| Burning position | Any |
|------------------|-----|

Country specific categorizations

| | |
|-----------------|-----------------|
| ANSI code | Other |
| Order reference | LOK-IT! 1200W/3 |

Logistical data

| | |
|----------------------------------|---------------|
| EAN 10 of contained light source | 4008321382795 |
|----------------------------------|---------------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---|------------------------------------|
| Date of Declaration | 01-04-2022 |
| Primary Article Identifier | 4008321382795 |
| Candidate List Substance 1 | No declarable substances contained |
| Declaration No. in SCIP database | No declarable substances contained |

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-------------------------------|---------------------------------|---|-----------------------|--------------|
| 4008321382795 | Lok-it! 1200 W 80 V/32/P50 | Folding carton box 1 | 70 mm x 70 mm x 160 mm | 0.78 dm ³ | 178.00 g |
| 4008321382801 | Lok-it! 1200 W 80 V/32/P50 | Shipping carton box 12 | 294 mm x 222 mm x 175 mm | 11.45 dm ³ | 2940.81 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.