



2015 Compact Wide Cardioid Microphone



2015 Compact Wide Cardioid Microphone

TABLE OF CONTENTS

Specifications - 2015	1
-----------------------	---

Specifications - 2015

Directional pattern	Wide cardioid
Principle of operation	Pressure gradient
Cartridge type	Pre-polarized condenser
Frequency response	20 Hz - 20 kHz
Effective frequency range, ± 2 dB, at 30 cm (11.8 in)	40 Hz to 18 kHz

Sensitivity, nominal, ± 2 dB at 1 kHz	12 mV/Pa; -37.7 dB re. 1 V/Pa
Equivalent noise level, A-weighted	Typ. 18 dB(A) re 20 μ Pa (max. 20 dB(A))
Distortion, THD < 1%	147 dB SPL (150 dB SPL peak)
Dynamic range	Typ. 132 dB
Max. SPL, THD 10%	150 dB SPL (153 dB SPL peak)
Switchable attenuator, filters etc.	-
Rated output impedance	60 Ω
Minimum load impedance	2 k Ω
Cable drive capability	100 m (328 ft)
Output balance principle	Impedance balancing with Active Drive
Common mode rejection ratio (CMRR) > 60 dB	
Power supply (for full performance)	P48 (Phantom Power)
Current consumption	0.7 mA
Connector	XLR-3M. Pin 1: shield, Pin 2: signal + phase, Pin 3: - phase
Color	Matte black
Weight	83 g (2.9 oz)
Microphone diameter	19 mm (0.75 in)
Capsule diameter	17 mm (0.67 in)
Microphone length	94 mm (3.7 in)
Maximum output voltage, RMS	8.7 V (21 dBu)
Polarity	+V at pin 2 for positive sound pressure
Temperature range	-40°C to 45°C (-40°F to 113°F)

Relative humidity (RH) Up to 90%

Sensitivity selection tolerance (at 1 kHz) ±1.5 dB

Typical on-axis response of a 2015 measured at 30 cm (11.8 in)

Typical directional characteristics of a 2015

