

Powersafe Insulated Horizontal Clamp

The Powersafe Insulated Horizontal Clamp is completely insulated which allows the user to connect directly to a low voltage busbar. The clamp is tightened onto the busbar with an insulated key tool which meets the requirements of IEC 60900 (live working hand tools for use up to 1000Vac / 1500Vdc).

A Powersafe connector (can be source or drain) is incorporated in the clamp to allow direct connection to the generator cable. The Horizontal Clamp is rated at 800A continuous.

The connectors on the clamps are also colour coded and keyed to distinguish between phases and prevent connection errors.

The head of the Horizontal Clamp is 45mm wide.

Picture shows a Horizontal Clamp Short Arm L1 Brown

These are also available with long arms and right angled arms.



Horizontal Clamp Short Arm with Source Connection

Part Number	Description
SD00165	HORIZONTAL CLAMP-E-GN-SHORT
SD00166	HORIZONTAL CLAMP-N-BL-SHORT
SD00167	HORIZONTAL CLAMP-L1-BN-SHORT
SD00168	HORIZONTAL CLAMP-L2-BK-SHORT
SD00169	HORIZONTAL CLAMP-L3-GY-SHORT

Horizontal Clamp Long Arm with Source Connection

SD00170	HORIZONTAL CLAMP-E-GN-LONG
SD00171	HORIZONTAL CLAMP-N-BL-LONG
SD00172	HORIZONTAL CLAMP-L1-BN-LONG
SD00173	HORIZONTAL CLAMP-L2-BK-LONG
SD00174	HORIZONTAL CLAMP-L3-GY-LONG

Horizontal Clamp Right Angled Arm with Source Connection

SD00175	HORIZONTAL CLAMP-E-GN-RIGHT ANGLED
SD00176	HORIZONTAL CLAMP-N-BL-RIGHT ANGLED
SD00177	HORIZONTAL CLAMP-L1-BN-RIGHT ANGLED
SD00178	HORIZONTAL CLAMP-L2-BK-RIGHT ANGLED
SD00179	HORIZONTAL CLAMP-L3-GY-RIGHT ANGLED