

Powersafe Insulated Mini G Clamp

The Powersafe Insulated Mini G Clamp is completely insulated which allows the user to connect directly to a low voltage busbar. The clamp is tightened onto the busbar with an insulated box spanner which meets the requirements of IEC 60900 (live working hand tools for use up to 1000Vac / 1500Vdc).

A Powersafe connector (can be source or drain) is incorporated in the clamp to allow direct connection to the generator cable. The Mini G Clamp is rated at 500A continuous.

The connectors on the clamps are also colour coded and keyed to distinguish between phases and prevent connection errors.

The head of the Mini G Clamp is 26mm wide.

Picture shows a G Clamp Mini Short Arm L1 Brown

These are also available with long arms and right angled arms.



G Clamp Mini Short Arm with Source Connection

Part Number	Description
SD00063	G-CLAMP MINI-E-GN-SHORT
SD00064	G-CLAMP MINI-N-BL-SHORT
SD00065	G-CLAMP MINI-L1-BN-SHORT
SD00066	G-CLAMP MINI-L2-BK-SHORT
SD00067	G-CLAMP MINI-L3-GY-SHORT

G Clamp Mini Long Arm with Source Connection

SD00203	G-CLAMP MINI-E-GN-LONG
SD00204	G-CLAMP MINI-N-BL-LONG
SD00205	G-CLAMP MINI-L1-BN-LONG
SD00206	G-CLAMP MINI-L2-BK-LONG
SD00207	G-CLAMP MINI-L3-GY-LONG

G Clamp Mini Right Angled Arm with Source Connection

SD00208	G-CLAMP MINI-E-GN-RIGHT ANGLED
SD00209	G-CLAMP MINI-N-BL-RIGHT ANGLED
SD00210	G-CLAMP MINI-L1-BN-RIGHT ANGLED
SD00211	G-CLAMP MINI-L2-BK-RIGHT ANGLED
SD00212	G-CLAMP MINI-L3-GY-RIGHT ANGLED

