

Insulated Overhead Line Clamp

The Powersafe Insulated Overhead Line Clamp is designed to allow direct connection of a generator unit to low voltage overhead line systems. The assembly consists of an insulated line clamp with 3m of flexible copper cable and a Powersafe Line Source connector.

These assemblies are available in different lengths and diameters of flexible HO7RN-F cable ranging from 50mm² up to 120mm².

The maximum current rating is 500A



Picture shows an Overhead Clamp
with a Source N-Blue connector

Overhead Line Clamp 3m tail and Source Connection

Part Number	Description
SD00034	Overhead Line Clamp E-EN-50mm
SD00030	Overhead Line Clamp N-BL-50mm
SD00031	Overhead Line Clamp L1-BN-50mm
SD00032	Overhead Line Clamp L2-BK-50mm
SD00033	Overhead Line Clamp L3-GY-50mm
SD00339	Overhead Line Clamp E-EN-70mm
SD00340	Overhead Line Clamp N-BL-70mm
SD00341	Overhead Line Clamp L1-BN-70mm
SD00342	Overhead Line Clamp L2-BK-70mm
SD00343	Overhead Line Clamp L3-GY-70mm
SD00201	Overhead Line Clamp E-EN-95mm
SD00001	Overhead Line Clamp N-BL-95mm
SD00002	Overhead Line Clamp L1-BN-95mm
SD00003	Overhead Line Clamp L2-BK-95mm
SD00004	Overhead Line Clamp L3-GY-95mm
SD00202	Overhead Line Clamp E-EN-120mm
SD00074	Overhead Line Clamp N-BL-120mm
SD00075	Overhead Line Clamp L1-BN-120mm
SD00076	Overhead Line Clamp L2-BK-120mm
SD00077	Overhead Line Clamp L3-GY-120mm