


Multisignal CAT6A, Audio and Power

eurocable 2CAT6SF 12/3 AD2, specifically designed to answer the growing needs to run different signals over one cable.

This cable includes 3x12 AWG (3,5 mm²) double shielded power cable, two AES individually jacketed and shielded audio pairs, plus two SF/UTP ethernet lines (maximum lenght 90 m).

The lenghts stated refer to the longest distance to obtain EIA/TIA 568.B.2 certification, hence the Ethernet backbone protocol. Therefore applications with other protocols may run longer lenghts.




CE

MOBILE

DIGITAL

JACKET COLOR ■

152 m ON WOODEN REELS



CVS LK2CAT6SF 12/3 AD2

- Two digital audio pairs.
- Two CAT6A cables.
- One 3 x 3.5 mm² power cable.

MADE IN ITALY



| | | | Audio | CAT6A | Power |
|--------------|-----------------------|----------------|---|--|------------------------------------|
| GENERAL DATA | | | | | |
| Cable | O.D. | 21.30 mm | 4.00 mm | 8 mm | 10.60 mm |
| | Weight | 46.9 Kg/100m | | | |
| | Standard reels | 152 m | - | - | - |
| | Volt. Rate | - | - | - | 600 V |
| | Operating temperature | -20°C/+ 70°C | | | |
| Jacket | Material | PVC | | | |
| | Nom. Thick. | 1.70 mm | 0.65 mm | 0.53 mm | - |
| | Color | Black | - | 1: Black - 2: Blue | - |
| | Power | UL - 758 CL 43 | | | |
| Shield | Material | - | Aluminium - Polyester tape plus 18 x 0.10 mm drain wire | Aluminium - Polyester tape plus drain wire | - |
| | Coverage | - | 100% | 100% | - |
| Conductor | Qty | - | 2 | 2 | 3 |
| | Strand | - | 18 x 0.10 mm | 1 x 0.58 mm | 70 x 0.25 mm |
| | Area/AWG | - | 0.14 mm²/26 | 0.22 mm²/24 | 3.44 mm²/12 |
| | Insul. O.D. | - | 1.20 mm | 1.00 mm | 1.00 mm |
| | Material | - | Annealed tinner copper polyolefine insulated | Solid bare copper polyolefine insulated | Annealed bare copper PVC insulated |