



Analog Video Cables

eurocable offers a wide range of video coaxial cable, suitable for all analog 50 ohm and 75 ohm video transmission. Shielded with copper braid and PVC jacketed to guarantee long life and high flexibility. Video coax cables according to the standard MILC17 requirements.

	
MOBILE	MOBILE
JACKET COLOR ■	JACKET COLOR ■
1000 m ON WOODEN REELS	1000 m ON WOODEN REELS
	
CVS LKRG58C17	CVS LKRG59C17
• 50 ohm compliant to MILC-17 standard.	• 75 ohm suitable for CCTV and MATV applications.



ELECTRICAL DATA			
D.C.R. at 20°C	Conductor	37.50 ohm/km	158 ohm/km
	Shield	17 ohm/km	14.80 ohm/km
Capacitance at 20°C		100 pF/m	67 pF/m
Nominal Impedance		50 ohm	75 ohm
Attenuation	10 MHz	2.50 db/100 m	2.00 db/100 m
	50 MHz	9.70 db/100 m	7.70 db/100 m
	100 MHz	13.90 db/100 m	10.70 db/100 m
	200 MHz	20.40 db/100 m	15.70 db/100 m
Vel. of Prop.		66%	
GENERAL DATA			
Cable	O.D.	5.00 mm	6.20 mm
	Standard reels	1000 m	
	Weight	3.70 Kg/100 m	5.09 Kg/100 m
	Operating temperature	-20°C/+70°C	
Jacket	Material	PVC	
	Nom. Thick.	0.75 mm	1.10 mm
Shield	Material	Tinned copper	Bare copper
		Braid shield	
	Coverage	93%	24%
Conductor	Qty	1	
	Strand	1 x 0.18 mm	7 x 0.58 mm
	Area/AWG	0.48 mm²/25	0.26 mm²/30
	Dielectric O.D.	2.95 mm	3.70 mm
	Material	Annealed tinned copper, polyethylene insulated	Coppered steel, polyethylene insulated

Not suitable for applications above 50 volt ac, 75 volt dc.