

## **Introducing the Incredible**

## FLARIEUR



Available with ((((•)))) **Wireless Option** 





Little brother of the fabulous Solaris LED Flare, winner **Live Design 2013 Product** of the Year and PLASA 2013 **Sustainability Award** 

**Super Bright LED RGBW** Wash/Strobe/Blinder



**MORE SAVINGS!** Simultaneous colour wash and strobe in ONE fixture – Saves labour, time, space, energy, and cost.

**MORE SMOOTH!** Instantaneous RGBW colour mixing with 1200Hz refresh rate – Smooth on-camera dimming.

**MORE VERSATILE!** Pixel-map feature divides into 1, 2, or 4 sections for ultimate control.

**MORE SATURATED COLOURS!** Intense, deep reds and blues. Ultra-bright greens. Brilliant camera-friendly whites.

**MORE FLEXIBLE!** 36-degree beam angle optimised for most applications.

Innovative, Performance-Driven Show Technology Since 1983

New York

+1 201-896-8600

Beijing

Toronto +1 519-538-0888

tmb.com



## FLARIEUR:

## **SPECIFICATIONS**

Light sources	32 10W CREE® LEDs (divided in to 4 pixels)
Beam spread	36°
Colours	4- R, G, B, W
Average colour wavelength (manufacturer rated)	Red: 625 nm
	Green: 530 nm
	Blue: 460 nm
	White: >5700K
Refresh rate	1200 Hz
Intensity control	16-bit or 8-bit
Control	DMX-512
Wireless control	Wireless option available by special order
AC power	90-277 VAC universal input, 50/60 Hz
Cooling	Air-cooled fan
Operating temperature	-20°C - +40°C
DMX channels	3-24 depending on control mode
DMX connectors	In/Out - XLR 5-pin F/M
Max. power draw	~400 W
Power connectors	In- PowerCon 20A blue + THRU- PowerCon grey
Fixing	Adjustable yoke
Fixture body	Powdercoated steel
Unit dimensions (HxWxD)	6.1 x 13.4 x 5.3 in (15.5 x 34 x 13.5 cm)
Shipping dimensions (HxWxD)	TBA
Unit weight	10.6 lb (4.8 kg)
Shipping weight	12 lb (5.4 kg)

Specifications and features are subject to change without notice.





