

xVision HDMI DA 4K
Specifications



Connections	Video Input	1 x HDMI 2.0a
	Video Output	4 x HDMI 2.0a Individual downscaling per port
Supported Signals	Video Formats	HDR 4K2K @ 60 fps (4:2:0 10 bits) 4K2K @ 60 fps (4:4:4 8 bits)
	HDCP Compliance	HDCP 2.2 / 1.4
	Video Bandwidth	Single-link 600MHz (18 Gbps)
	Embedded audio support	DTS-HD Master Audio,Dolby TrueHD Dolby Digital, DTS, LPCM
Physical Specifications	Height	50 mm (1.97 in)
	Depth	180 mm (7.08 in)
	Width	107 mm (4.21 in)
	Weight	1 kg (2.2 lbs)
Environnemental Specifications	Operating temperature	0-40C
	Operating humidity	0-90% RH non-condensing
Power Requirements	Power Supply	Built-in power supply PowerCon True1 input / PowerCon True1 input
		PowerCon input / Edison 5-15 output

Power Consumption	25 W
Operational Voltage Range Courtesy Outlet	90-250V 50-60Hz with True1 connectors Max 10A, same voltage as input

In the Box

xVision Streaming Server
AC Mains PowerCon cable (1.5m, specify plug
type at ordering)

Certification & Compliance

CAN/CSA-C22.2 NO.60950
UL 60950
FCC Part 15 Class A
CE