



STRIKE P38

STRIKE P38 is a compact, punchy and outdoor-ready blinder and strobe powered by a 90 W warm white LED source. An emulated “amber shift” warms the Color Temperature of the light as it dims to perfectly mimic incandescent lights. The unit’s IP-rated fan keeps it cool enough for use as a wash, while IP-rated direct power and DMX connections eliminate undesirable whips. Control it with adjustable PWM and RDM for added flexibility.



At a Glance

- Intense single pod blinder/strobe rated IP65 for all-weather use
- Emulated “red shift” to mimic incandescent fixtures perfectly.
- 16-bit dimming control for smooth, perfect fades
- Strobe functionality for high-impact effects on-the-fly
- Easy to use OLED display
- Adjustable Pulse Width Modulation (PWM)
- RDM (Remote Device Management) for added flexibility

Specifications

Optical

- Light Source: 1 LED (WW) 90 W, (1.19 A), 2688 K, 50,000 hours life expectancy.
- Light Source: 8 LEDs (Amber) 5 W, (0.07 A), 50,000 hours life expectancy.
- Color Temperature (at full): 2754 K
- Color Temperature (at 10%): 1899 K
- CRI: 92
- Beam Angle: 27°
- Field Angle: 51°
- Lumens: 2,186
- Illuminance: 325 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 25,000 Hz

Dynamic Effects

- Dimmer: Electronic
- Strobe Rate: 0 to 29 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

Construction / Physical

- Dimensions: 11.93 x 10.27 x 7.25 in (303 x 261 x 184 mm)
- Weight: 8.4 lb (3.8 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast
- Accessory Holder/Gel Frame Size: 6.25 in (159 mm)

Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP65 XLR
- Cable Length (power): 5 ft (1.5 m)

Control

- Protocol(s): DMX, RDM
- DMX Channels: 1, 3, 4, 5 or 6
- Modes/Personalities: 5 personalities (1ch, 3ch, 4ch, 5ch, 6ch)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 30 units @ 120 V; 50 units @ 208 V; 55 units @ 230 V
- Power and Current: 54 W, .449 A @ 120 V, 60 Hz
- Power and Current: 56 W, .267 A @ 208 V, 60 Hz
- Power and Current: 58 W, .245 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE, MET
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

- STRIKE P38

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN

- Seetronic Powerkon IP65 power cord
- Gel frame (6.25 in/158.75 mm accessories)

- Seetronic Powerkon power linking cables
- 5-pin IP or Non-IP DMX Cables
- Ovation F6.25 Barndoor