



## Ovation P-56UV

Ovation P-56UV is a compact, virtually silent par and the first of its kind to produce a flat and even field of true UV light with minimal projected visibility via a homogenized, single-source LED. Interchangeable lens plates are included for wide beam angles and the unit accepts standard 7.5" beam shaping accessories. Ideally suited for theatrical and studio applications, the virtually silent and bright par also features extremely smooth 16-bit dimming, as well as RDM and PWM for set-up ease.



### At a Glance

- True (365 nm) UV light with homogenized single source
- Minimal projected visible light
- Quiet operation for use in any situation with fan speed control
- RDM and variable Pulse Width Modulation for setup ease
- Accepts standard 7.5" beam shaping accessories
- Selectable dimming curves for smooth fades or snap-on use
- 16-bit dimming resolution for smooth fades
- Compact design with homogenous single source of blacklight

# Specifications

## Optical

- Light Source: 1 LEDs (1UV) 114 W, (3 A), 50,000 hours life expectancy
- Coverage Angle (Wide Lens): 56°
- Radiant Power: 33022mW
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

## Dynamic Effects

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 29 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

## Construction / Physical

- Dimensions: 12.48 x 12.83 x 14 in (317 x 326 x 363 mm)
- Weight: 12 lb (5.4 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast
- Accessory Holder/Gel Frame Size: 7.5 in (191 mm)

## Connections

- Power Connection: Edison (Local) plug to Neutrik powerCON
- Power Input: Neutrik powerCON
- Power Output: Neutrik powerCON
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

## Control

- Control Protocol: DMX, RDM
- DMX Channels: 1, 2, 3 or 6
- Modes/Personalities: 4 personalities (1, 2, 3, 6)

## Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 13 units @ 120 V; 21 units @ 208 V; 23 units @ 230 V
- Power and Current: 125 W, 1.03 A @ 120 V, 60 Hz
- Power and Current: 130 W, .62 A @ 208 V, 60 Hz
- Power and Current: 136 W, .58 A @ 230 V, 50 Hz

## Certifications / Qualifications

- CE, MET
- IP Rating: IP20, dry location
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

## What's Included

- Ovation P-56UV
- Neutrik powerCON power cord
- Gel frame holder (7.5 in/191 mm accessories)

## Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Neutrik® powerCON® cables
- 3-pin or 5-pin DMX Cables
- Ovation P-56UV
- DF60X1D – 60x1 deg Color Blending Filter

## Ordering Info

- Item Code: 03031499