

## Product data sheet

### Characteristics

# PDL681M20HWH

Switch 600 Series Mechanism - Single-pole - 1-gang - Marked HEAT-OFF - 250 V - 20 A / 16 AX - White



### Main

|                           |            |
|---------------------------|------------|
| Range of product          | 600 Series |
| Product or component type | Switch     |
| Control type              | Rocker     |

### Complementary

|                                       |                                                    |
|---------------------------------------|----------------------------------------------------|
| Material                              | PC (polycarbonate)                                 |
| Colour tint                           | White                                              |
| Surface finish                        | Gloss                                              |
| Installation direction                | Vertical<br>Horizontal                             |
| Length                                | 23 mm                                              |
| Width                                 | 23 mm                                              |
| Depth                                 | 26 mm                                              |
| Rated current                         | 20 A<br>16 AX                                      |
| [Ue] rated operational voltage        | 250 V                                              |
| Network type                          | AC                                                 |
| Motor M-rating AS3133                 | M60                                                |
| Network number of phases              | 1 phase                                            |
| Number of gangs                       | 1 gang                                             |
| Number of poles                       | 1                                                  |
| Mounting mode                         | Front                                              |
| Ambient air temperature for operation | -10...40 °C                                        |
| Cable cross section                   | 2 x 2.5 mm <sup>2</sup><br>4 x 1.5 mm <sup>2</sup> |

### Offer Sustainability

|                          |                                                                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive        | Will be compliant – Date to be confirmed                                                                                          |
| Environmental Disclosure |  <a href="#">Product Environmental Profile</a> |