

## Product data sheet

### Characteristics

# PDL680M32WH

Switch 600 Series Mechanism - Single-pole - 1-gang - Marked OFF-AIRCON - 250 V - 32 A / 20 AX - White




### Main

|                           |            |
|---------------------------|------------|
| Range of product          | 600 Series |
| Product or component type | Switch     |
| Control type              | Rocker     |

### Complementary

|                                       |                       |
|---------------------------------------|-----------------------|
| Material                              | PA (polyamide)        |
| Colour tint                           | White                 |
| Surface finish                        | Gloss                 |
| Installation direction                | Vertical              |
| Length                                | 23 mm                 |
| Width                                 | 23 mm                 |
| Rated current                         | 20 AX<br>32 A         |
| [Ue] rated operational voltage        | 250 V                 |
| Network type                          | AC                    |
| Motor M-rating AS3133                 | M180                  |
| Network number of phases              | 1 phase               |
| Number of gangs                       | 1 gang                |
| Number of poles                       | 1                     |
| Mounting mode                         | Front                 |
| Ambient air temperature for operation | -10...40 °C           |
| Cable cross section                   | 2 x 6 mm <sup>2</sup> |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| EU RoHS Directive        | Will be compliant – Date to be confirmed  |
| Environmental Disclosure |  <a href="#">Product Environmental Profile</a> |