

DESCRIPTION

A powerful and versatile tool for creating subtle or dynamic, realistic or extravagant, beautiful or arresting lighting effects by rotating one or two B size metal or glass gobos.

Simple, silent, sophisticated. The SimpleSpin™, a member of Rosco's new BeltDriveFX series of equipment, has been engineered from the ground up to give the designer and technicians all the features they need in a basic gobo rotator without the bloat of unnecessary and expensive add-ons.

One motor, two gobos. The SimpleSpin™ is a variable speed device capable of rotating two gobos in opposing direction. "Set and Forget" on-board speed control and direction switch. *Simple.*

Silicon Belt Drive. Hi temperature silicon belts provide positive, reliable drive without squeaks, clicks, shrills or chatter. In a TV studio, intimate black box theatre, office lobby or church service. *Silent.*

Advanced controls. Internal, universal power supply at 100-240VAC 50/60hz for world-wide installations. Dimmer Remote feature to control speed by connecting the SimpleSpin™ to a dimmer. *Sophisticated*



BeltDriveFX Advances

- High temperature silicon belt for smooth, silent and reliable operation;
- Modern stepper motor drives with advanced electronic controls provides speed from 0.5rpm to 24rpm with no risk of stalling;
- Simple, intuitive and user friendly operator modes provide maximum flexibility for programmers of all abilities;
- Threaded gobo collar insures secure fit for any type of gobo – thin metal to thick effects glass.
- Friction Lock™ secure fit mechanism holds the rotator tightly in the iris slot even when the lens barrel is rotated around.

SPECIFICATIONS

Electrical		Physical	
Input	100-240VAC 50/60hz	Size (W x H x D)	4.67in x 10.375in x 0.53/2.4in 119mm x 263.5mm x 13.5/62mm
Connector	IEC C13	Weight	22.4 oz (0.63Kg)
Power Draw	1A max		
Operation		Luminaires	
Speed	0.5 - 24 rpm	Standard Iris Slot luminaires: ETC Source 4, ETC S4 Zoom, Selecon Pacific, Selecon Pacific Zoom, Philips SPX, Strand SL, Altman Shakespeare, Leviton Leo	
Control	Manual or Dimmer Remote		
Gobos	86mm Std B Size (metal or glass) Apollo B (80mm) metal or glass 86mm OD x 75mmIA x 3.5mm thick (maximum dimensions)		

PRODUCT NUMBERS

205 63100 0000 SimpleSpin™ Dual Gobo Rotator 100-240v

Parts and Accessories

205 65310 0000 Simple Spin Silicon Drive Belts Set of 2 (A - 139mm x 3.5, B - 148mm x 3.5)
205 65002 0001 Gobo Wheel - Threaded Collar
226 19903 0119 IEC Power Cord – Parallel Blade "Edison" Connector
205 83007 0000 Gobo Spacer Ring

